

SERIES / ZEN

ZEN

ADDRESS FURNITURE. TABLES, CABINETS AND BLOCKS
DRAWERS



Polígono La Portalada II / Cordonera, 5
CP 26006 – LOGROÑO (La Rioja)
Phone: 941-230752
Fax: 941-248977

ismobel.com

TABLE OF CONTENTS

- 1 / PRODUCT DESCRIPTION
- 2 / PHOTOGRAPHS
- 3 / REGULATIONS
- 4 / FINISHES
- 5 / PICTOGRAMS

1/

DESCRIPTION

AND TECHNICAL CHARACTERISTICS

Description of the product offered /

- Table tops made of 25mm chipboard. thick, finished in bilaminate (made with PEFC certification). Finish to choose from all our designs.
- Optionally they can be served in:
 - .1 Safety glass 6+6mm. matt finish
 - .2 Stratified finish on chipboard (HPL)
 - .3 Phenolic (COMPACMEL)
 - .4 Natural varnished wood veneer on chipboard.
- 2mm PVC/ABS straight edges. thick applied with hot melt glue (100% recyclable) with all rounded edges with radius 2mm.
- The cover can have a cable gland hole with a trim cover or a TOP ACCESS (metallic or plastic) located in the place indicated by the property and in the chosen finish.
- Gantry legs in the shape of an inverted U, made of pickled and cold-rolled steel profiles with a square section of 50x50x1.5mm. and rectangular section 50x25x2mm. for the horizontal part that joins the legs.
- It incorporates two metal beams made of pickled and cold-rolled steel profiles with a rectangular section of 40x30x1.5mm. anchored under the table and set back 150mm. from the envelope
- Optionally, the leg can be manufactured with its lower part closing the frame, with a 50x25x2mm rectangular section tube. on all its faces
- Coating of metal parts in epoxy powder paint with 80 microns prior to phosphating. Antioxidant, guaranteeing 200 hours of saline mist. Characteristics:
 - .1 Resistance to chemical agents for domestic use UNE 48027:1980 5 (24H), 4 (72H).
 - .2 Resistance to mechanical damage: UNE-EN ISO 2409:2007 Classification: 0.
 - .3 Drop of a mass: UNE-EN ISO 6272-1:2004, at 500 mm without cracking.
 - .4 Resistance to humidity: UNE-EN ISO 6270-1:2002 without alteration.
 - .5 Accelerated aging: UNE EN ISO 11507:2007 24H loss of gloss
- Height adjustment (+/- 3cm.) by means of PP levelers with a diameter of 50mm. and M10, black, with non-slip sole included in the legs. Table height 740mm.
- Joining the deck to the structure by means of "metal to metal" joints.
- The structure complies with the following regulations:
 - .1 Regarding dimensions: EN 527-1:2000 Aptd 3,4,5.
 - .2 Regarding safety requirements: EN 527-2:2002 Aptd 3,4
 - .3 Regarding mechanical tests: EN 527-3:2003 Aptd 6.1 to 6.6.
- It can incorporate a front skirt in the same finish as the 19mm table. thick, attached to the support structure by metal brackets. The skirt can also be metallic.
- Possibility of adapting separating panels of the same material as the countertops, upholstery, sound absorbing, methacrylate or glass.

- It can incorporate a metal electrification duct for cable collection. This is attached to the support structure and is placed along the board. Made of 1 mm steel sheet. There are different sizes and individual or double for the BENCH format posts.
- There is the possibility of incorporating large-capacity central electrification with double folding cover with hidden hinge. This solution allows easy access to the entire electrification tray.
- In addition, to raise cables from the ground to the electrification channel, a plastic cable gland profile (vertebra) is used, a totem made of an aluminum profile or a metallic accessory finished to match the structure.
- In the case of incorporating a table wing, it has the same characteristics as the table. (top, leg and double frame that connects with the frame of the table forming a stable and robust set) • The meeting tables use a metal base foot structure capable of guaranteeing the support of the table.
board without swings, or, the same structure as the tables previously described. • There are socket boxes prepared to be coupled or embedded in the different tables of the series.

2/ PHOTOGRAPHS







3/

NORMATIVE

Regulations that it complies with (Annexes are attached)

- ISO 9001 quality certificate.
- ISO 14001 Environmental Certificate.
- TECNALIA quality mark certificate.
- TECNALIA product certificate.

4/

FINISHES

