

SERIES / DELPHI

# DELPHOS

COMPREHENSIVE OFFICE EQUIPMENT. TABLES, CABINETS and  
DRAWER BLOCKS



Polígono La Portalada II / Cordonera, 5  
CP-26006 – LOGROÑO (La Rioja)  
Telephone: 941-230752  
Fax: 941-248977  
[ismobel.com](http://ismobel.com)

## INDEX CONTENTS

- 1 / PRODUCT DESCRIPTION
- 2 / PHOTOGRAPHS
- 3 / REGULATIONS
- 4 / FINISHES
- 5/ PICTOGRAMS

1/

## DESCRIPTION AND TECHNICAL CHARACTERISTICS

### Description of the product offered /

- Table tops made of 25mm particle board. thick, bilaminated finish (made with PEFC certification). Finish to choose from all our designs.
  - Optionally they can be served in: 1 6+6mm
    - safety glass. matte finish 2 Laminated finish on
    - chipboard (HPL)
    - 3 Phenolic (COMPACMEL)
    - 4 Varnished natural wood veneer on chipboard.
  - 2mm PVC/ABS straight edges. thick applied with hot melt glue (100% recyclable) with all edges rounded with a 2mm radius.
  - The cover may have a cable gland hole with a decorative cover or a TOP ACCESS (metal or plastic) located in a place indicated by the property and in the chosen finish.
  - Inverted U-shaped gantry legs, made of pickled and cold-rolled steel profile with a square section of 50x50x1.5mm. and with a rectangular section of 40x25x2mm. for the horizontal part that joins the legs.
  - Includes a metal beam made of pickled and cold-rolled steel profile with a rectangular section of 40x30x1.5mm. anchored below the table centered on the envelope.
  - Coating of the metal parts in 80 micron epoxy powder paint after phosphating.
- Antioxidant, guaranteeing 200 hours of salt fog. Characteristics: 1 Resistance to
- chemical agents for domestic use UNE 48027:1980 5 (24H), 4 (72H).
  - 2 Resistance to mechanical damage: UNE-EN ISO 2409:2007 Classification: 0.
  - 3 Drop of a mass: UNE-EN ISO 6272-1:2004, at 500 mm without cracking.
  - 4 Resistance to humidity: UNE-EN ISO 6270-1:2002 without alteration.
  - 5 Accelerated aging: UNE EN ISO 11507:2007 24H loss of gloss · Height adjustment (+/- 3cm.) using PP levelers with a diameter of 50mm. and M10, black color, with non-slip sole included on the legs. Table height 740mm.
- Union of the board to the structure using "metal to metal" joints.
  - The structure complies with the following regulations: 1
    - Regarding dimensions: EN 527-1:2000 Aptd 3,4,5.
    - 2 Regarding safety requirements: EN 527-2:2002 Aptd 3,4 3 Regarding
    - mechanical tests: EN 527-3:2003 Aptd 6.1 to 6.6.
  - It can incorporate a front skirt in the same finish as the 19mm table. thick, attached to the support structure using metal fastening brackets. The skirt can also be metallic.
  - Possibility of adapting separator panels made of the same material as the countertops, upholstered, sound-absorbing, methacrylate or glass.
  - It can incorporate a metal electrification channel for collecting cables. This is attached to the support structure and is placed along the board. Made of 1 mm steel sheet. They come in different sizes and single or double for seats in BENCH format.

- There is the possibility of incorporating large-capacity central electrification with a double folding cover with hidden hinge. This solution allows easy access to the entire electrification tray. • In addition, to raise cables from the ground to the electrification channel, a plastic cable gland profile (vertebra), a totem made of aluminum profile or a metal accessory finished to match the structure is used.
- In the case of incorporating a table wing, it has the same characteristics as the table. (top, leg and double frame that connects with the frame of the table, forming a stable and robust assembly) • The meeting tables use a metal pedestal base structure capable of guaranteeing the support of the tabletop without swinging, or, the same structure than the tables previously described.
- There are socket boxes prepared to be attached or recessed into the different tables in the series.

2/

## PHOTOGRAPHS







### 3/ NORMATIVE

Regulations that comply (Appendixes are attached)

- ISO 9001 quality certificate.
- ISO 14001 Environmental Certificate.
- ISO 14006 ECODESIGN Certificate.
- TECNALIA quality mark certificate.
- TECNALIA product certificate.

### 4/ FINISHES



**ACABADOS** 

**ELEMENTOS VERTICALES**  
VERTICAL ELEMENTS / ÉLÉMENTS VERTICAUX

					
AZUL BLUE BLEU	VERDE PISTACHO GREEN PISTACHO VERT PISTACHE	AMARILLO YELLOW JAUNE	NARANJA ORANGE ORANGE	ROJO RED ROUGE	NEGRO BLACK NOIR

**ENCIMERAS BARNIZADAS**  
WOOD VENEER / BOIS VERNIS

						
CENIZA ASH CENDRE	ROBLE OAK CHÊNE	WENGÉ WALNUT WENGÉ	CEREZO CHERRY CERISIER	LACA BLANCA WHITE LACQUER LAQUE BLANC	LACA NEGRA BLACK LACQUER LAQUE NOIR	LACA A ELECCIÓN OTHER LACQUER LAQUE À CHOIXIR

**METÁLICOS**  
METAL / MÉTALLIQUE

			
NEGRO BLACK NOIR	BLANCO WHITE BLANC	GRIS ALUMINIO ALUMINIUM GREY GRIS ALUMINIUM	CRÓMO CHROME CHROME

  
**ISMOBEL**  
 Polígono La Portalada II  
 C/ Cordonera 5  
 T +34 941 230 752  
 E 230752@logroño (LA RIOJA) - (ESPAÑA)  
 ismobel@ismobel.com  
 ismobel.com